

Laminated & self-adhesive film

technical data sheet

Milky White 2022

MAXIMUM SIZE	Width: 150 cm Length: 330 cm
SHEET SIZE AND SHAPE	Can be customized to meet the user needs
THICKNESS	0,12 mm (laminated) 0,26 mm (self-adhesive)
VISIBLE LIGHT TRANSMITTANCE	On: >87% Off: >76%
UV PROTECTION	>98%
HAZE	On: <4% Off: >96%
IR BLOCK	> 60%
SHGC Solar Heat Gain Coefficient	On: 0.82 Off: 0.66
VIEWING ANGLE	160°
MAXIMUM POWER CONSUMPTION	5~10 W/ m ²
RESPONSE TIME	Off to On: < 0,01 s On to Off: <0,2
OPERATING VOLTAGE	48 V AC 50/60 Hz



Switchfilm Srl

www.switchfilm.it

info@switchfilm.it



Laminated & self-adhesive film technical data sheet

Milky White 2022

POWER ON	Transparent
POWER OFF	Opaque
WARRANTY	5 Years
WORKING TEMPERATURE	-10° C to 65° C
MODE	On / Off / Dimmable
CONTROL	Switch / Remote / Sensors
COLOR	Milky White
DELIVERY AS ROLL	Yes
CURVATURE	Possible
INSTALLATION	Adhesive Film onto Glass or between Glass sheets
PROJECTION	Rear Projection Suggested
SCREEN RATIO	Flexible based on Projector Type



Switchfilm Srl

www.switchfilm.it

info@switchfilm.it

